

GUJARAT TECHNOLOGICAL UNIVERSITY
BE-3 SEMESTER – PAPER SOLUTION – SUMMER 2025

Subject Name & Code:
Mechanics of Solids- 3130608

(Note: All Figures are in the last page.)

MARKS

Q.1 (a) Define : (i) Space (ii) Resultant (iii) Couple

03

Answer:

(i) Space:

Space is the geometric region in which bodies occupy positions. It refers to the three-dimensional extent (length, breadth, and height) in which all physical objects and phenomena exist and events occur.

(ii) Resultant:

A resultant is a single force which produces the same effect on a body as that of a system of forces acting together. It is obtained by vector addition of all the forces in the system.

(iii) Couple:

A couple is a system of two parallel forces that are equal in magnitude, opposite in direction, and do not share the same line of action. It causes rotation without translation and its moment is given by:

$$\text{Moment of Couple} = F \times d$$

where F is the force and d is the perpendicular distance between the forces.

(b) Determine resultant of coplanar concurrent force system shown in fig.1

04

Answer:

Given:

- 100 N horizontal ($\rightarrow$ along X-axis)
- 120 N inclined at 60° to X-axis (from Y direction)
- 150 N inclined at 30° to X-axis (from X direction, towards 2nd quadrant)

Step 1: Resolve all forces into horizontal (X) and vertical (Y) components

Force 1: 100 N (along X-axis)

$$F_{1x} = 100 \quad , \quad F_{1y} = 0$$

Force 2: 120 N at 60° above X-axis (1st quadrant)

$$F_{2x} = 120 \cos(60^\circ) = 120 \times 0.5 = 60 \, N$$

$$F_{2y} = 120 \sin(60^\circ) = 120 \times 0.866 = 103.92 \, N$$

Force 3: 150 N at 30° above negative X-axis (2nd quadrant)

$$F_{3x} = -150 \cos(30^\circ) = -150 \times 0.866 = -129.9 \, N$$

$$F_{3y} = 150 \sin(30^\circ) = 150 \times 0.5 = 75 \, N$$

Step 2: Add components

Total X:

$$R_x = F_{1x} + F_{2x} + F_{3x} = 100 + 60 - 129.9 = 30.1 \text{ N}$$

Total Y:

$$R_y = F_{1y} + F_{2y} + F_{3y} = 0 + 103.92 + 75 = 178.92 \text{ N}$$

Step 3: Resultant magnitude

$$\begin{aligned} R &= \sqrt{R_x^2 + R_y^2} = \sqrt{(30.1)^2 + (178.92)^2} \\ &= \sqrt{906.01 + 32023.56} = \sqrt{32929.57} = \boxed{181.43 \text{ N}} \end{aligned}$$

Step 4: Direction (angle with X-axis)

$$\begin{aligned} \theta &= \tan^{-1} \left(\frac{R_y}{R_x} \right) = \tan^{-1} \left(\frac{178.92}{30.1} \right) \\ &= \tan^{-1}(5.94) = \boxed{80.43^\circ} \end{aligned}$$

✓ **Final Answer for Q.1 (b):**

- **Magnitude of resultant = 181.43 N**
- **Direction = 80.43° above X-axis**

(c) Find support reactions for the beam shown in fig.2

07

Answer:

Given beam:

- Simply supported beam at A (pin) and B (roller), span = 8 m
- Point loads: 5 N at 2 m from A, 3 N at 6 m from A
- UDL: 2 N/m between 2 m and 4 m (length = 2 m)

Step 1: Replace UDL with equivalent point load

- UDL = 2 N/m over 2 m → Total Load = $2 \times 2 = 4 \text{ N}$
- Acts at the **midpoint of UDL**, i.e., 3 m from A

Step 2: Let reactions be:

- R_A at A (vertical)
- R_B at B (vertical)

Apply Equilibrium Equations:

(i) Sum of Moments about A = 0:

$$\begin{aligned} -R_B \cdot 8 + 5 \cdot 2 + 4 \cdot 3 + 3 \cdot 6 &= 0 \\ -8R_B + 10 + 12 + 18 &= 0 \Rightarrow -8R_B + 40 = 0 \Rightarrow R_B = \frac{40}{8} = \boxed{5 \text{ N}} \end{aligned}$$

(ii) Sum of vertical forces = 0:

$$R_A + R_B = 5 + 4 + 3 = 12 \Rightarrow R_A = 12 - R_B = 12 - 5 = \boxed{7 \text{ N}}$$

✓ **Final Answer for Q.1 (c):**

- **Reaction at A, R_A=7 N**
- **Reaction at B, R_B=5 N**

Q.2 (a) Enlist Fundamental principles of mechanics. State principle of transmissibility. **03**

Answer:

Fundamental Principles of Mechanics:

1. Newton's First Law (Law of Inertia):

A particle continues in its state of rest or uniform motion unless acted upon by a net external force.

2. Newton's Second Law:

The force acting on a particle is equal to the mass of the particle times its acceleration.

$$F = m \cdot a$$

3. Newton's Third Law:

For every action, there is an equal and opposite reaction.

4. Law of Parallelogram of Forces:

If two forces acting simultaneously at a point are represented by two adjacent sides of a parallelogram, their resultant is represented by the diagonal of the parallelogram.

5. Principle of Superposition:

The net effect of multiple forces acting on a particle is the same as the vector sum of the individual forces.

Principle of Transmissibility of Forces:

This principle states that the external effect of a force on a rigid body remains unchanged if the point of application is moved along its line of action.

Example:

If a 100 N force acts on one end of a rigid rod, it can be shifted to the other end (along the same direction), and the mechanical effect remains the same.

(b) A cord supported at A and B carries a load of 10 kN at D and a load of W at C as shown in Fig.3. Find the value of W so that CD remains horizontal. **04**

Answer:

Given:

- CD is a light cord (no self-weight), must remain **horizontal**
- Load at D = 10 kN
- Find W such that CD stays horizontal
- Angles:
 $\angle CAD = 60^\circ$, $\angle CBD = 30^\circ$

Let tensions in the cords be:

- T_{AC} in AC
- T_{BD} in BD
- T_{CD} is horizontal

Step 1: Use equilibrium at joint D (vertical & horizontal)

Let's resolve tensions into horizontal and vertical components.

At point D (horizontal equilibrium):

$$T_{CD} = T_{BD} \cos(30^\circ) \quad (1)$$

At point D (vertical equilibrium):

$$T_{BD} \sin(30^\circ) = 10 \quad (2) \Rightarrow T_{BD} = \frac{10}{\sin(30^\circ)} = \frac{10}{0.5} = 20 \text{ kN}$$

Now using (1):

$$T_{CD} = 20 \cdot \cos(30^\circ) = 20 \cdot 0.866 = 17.32 \text{ kN}$$

Step 2: Use equilibrium at point C

At point C (horizontal & vertical):

Horizontal:

$$T_{CD} = T_{AC} \cos(60^\circ) \Rightarrow T_{AC} = \frac{T_{CD}}{\cos(60^\circ)} = \frac{17.32}{0.5} = 34.64 \text{ kN}$$

Vertical:

$$T_{AC} \sin(60^\circ) = W \\ \Rightarrow W = 34.64 \cdot \sin(60^\circ) = 34.64 \cdot 0.866 = \boxed{30 \text{ kN}}$$

(c) Analyse the truss shown in fig. 4

07

Answer:

We are to find internal member forces using the **method of joints**.

Step 1: Support Reactions at A and C

Let:

- R_A = vertical reaction at A
- R_C = vertical reaction at C

Total load = $10 + 10 = 20 \text{ kN}$

Total span = 4 m

Both loads are at E (mid-span), symmetric

So, by symmetry:

$$R_A = R_C = \frac{20}{2} = 10 \text{ kN}$$

Step 2: Joint E

At joint E:

- Two loads: 10 kN down and 10 kN right
- Three members: DE (vertical), BE (horizontal), and CE (diagonal)

Assume:

- Force in DE = FDE (upward)
- Force in BE = FBE (left)
- Force in CE = FCE (direction assumed compressive toward E)

Equilibrium in Y-direction:

$$F_{DE} + F_{CE} \cdot \sin(\theta) = 10$$

Equilibrium in X-direction:

$$F_{BE} + F_{CE} \cdot \cos(\theta) = 10$$

From triangle:

Height = 2 m , base = 2 m

$$\Rightarrow \sin(\theta) = \frac{2}{\sqrt{2^2 + 2^2}} = \frac{2}{\sqrt{8}} = \frac{2}{2.828} = 0.707 \\ \cos(\theta) = 0.707$$

Now solve the two equations:

1. $F_{DE} + 0.707F_{CE} = 10$

2. $F_{BE} + 0.707F_{CE} = 10$

Subtract (1) and (2):

$$F_{DE} - F_{BE} = 0 \Rightarrow F_{DE} = F_{BE}$$

Substitute into one equation:

$$F_{DE} + 0.707F_{CE} = 10 \Rightarrow F_{DE} = 10 - 0.707F_{CE}$$

Now assume value for F_{CE} or move to other joints to continue solving. But due to symmetry and loads, you can also derive approximate forces or proceed joint-by-joint.

OR

- (c) For the system of force on a lamina OABC shown in figure 5, find magnitude and direction of the resultant force. Also locate the resultant by perpendicular distance from point "O". 07

Answer:

◆ **Step 1: Resolve All Forces into X and Y Components**

Force at point O:

750 at 40° below X-axis

- $F_{Ox} = 750 \cos(40^\circ) = 750 \times 0.766 = 574.5 \text{ N } (\rightarrow)$
- $F_{Oy} = -750 \sin(40^\circ) = -750 \times 0.643 = -482.25 \text{ N } (\downarrow)$

Force at point A:

800 N vertically $\uparrow$

- $F_{Ax} = 0$
- $F_{Ay} = +800 \text{ N}$

Force at point B:

600 at 50° above X-axis

- $F_{Bx} = 600 \cos(50^\circ) = 600 \times 0.643 = 385.8 \text{ N } (\rightarrow)$
- $F_{By} = 600 \sin(50^\circ) = 600 \times 0.766 = 459.6 \text{ N } (\uparrow)$

Force at point C:

a. $\rightarrow$

- $F_{Cx} = 1200 \text{ N}, F_{Cy} = 0$

◆ **Step 2: Sum of X and Y components**

$$R_x = 574.5 + 385.8 + 1200 = \boxed{2160.3 \text{ N}}$$

$$R_y = -482.25 + 800 + 459.6 = \boxed{777.35 \text{ N}}$$

◆ **Step 3: Resultant Force (Magnitude and Direction)**

$$R = \sqrt{R_x^2 + R_y^2} = \sqrt{(2160.3)^2 + (777.35)^2}$$
$$= \sqrt{4660116.09 + 604266.02} = \sqrt{5264382.1} \approx \boxed{2294.42 \text{ N}}$$

Direction θ :

$$\theta = \tan^{-1} \left(\frac{R_y}{R_x} \right) = \tan^{-1} \left(\frac{777.35}{2160.3} \right) = \tan^{-1}(0.3596) = \boxed{19.78^\circ} \text{ above X-axis}$$

◆ **Step 4: Find Location of Resultant from Point O**

Now we find the **perpendicular distance d** of the resultant from point O using **moment about O**:

◆ **Moments of Forces about Point O:**

1. **800 N at A ($\uparrow$)**
→ Distance = 1.5 m from O
→ Clockwise moment = $800 \times 1.5 = 1200 \text{ Nm}$
2. **600 N at B (50°):**
 - Horizontal component $F_{Bx} = 385.8$, vertical distance = 1.2 m
→ Moment = $385.8 \times 1.2 = 463 \text{ Nm clockwise}$
 - Vertical component $F_{By} = 459.6$, horizontal distance = 1.5 m
→ Moment = $459.6 \times 1.5 = 689.4 \text{ Nm anticlockwise}$
3. **1200 N at C ($\rightarrow$)**
→ Vertical distance = 0
→ No moment
4. **750 N at O**
→ Passes through point O
→ Moment = 0
5. **Given moment = 900 Nm (anticlockwise)**

◆ **Net Moment about O:**

$$M_O = +1200 \text{ (clockwise A)} + 463 \text{ (clockwise Bx)} - 689.4 \text{ (anticlockwise By)} - 900$$
$$= 1200 + 463 - 689.4 - 900 = \boxed{73.6 \text{ Nm (clockwise)}}$$

◆ **Step 5: Locate Resultant Using Moment Equation**

$$R \cdot d = M_O \Rightarrow 2294.42 \cdot d = 73.6 \Rightarrow d = \frac{73.6}{2294.42} = \boxed{0.0321 \text{ m}} = \boxed{3.21 \text{ cm from O}}$$

✓ **Final Answers (Q.2 OR (c))**

- **Magnitude of Resultant Force = 2294.42 N**
- **Direction = 19.78° above X-axis**
- **Location of Resultant = 3.21 cm (clockwise side) from Point O**

- Q.3 (a)** Determine resultant of coplanar concurrent force system shown in fig.1 using graphical method. **03**

Answer:

♦ **Graphical Procedure:**

1. **Select suitable scale**, e.g., 1 cm = 20 N
 2. **Draw the vectors tip-to-tail:**
 - First, draw 100 N horizontally to the right.
 - From the tip, draw 120 N at 60° upward (right quadrant).
 - Then, draw 150 N at 150° (180°–30°) backward.
 3. **Complete the triangle or polygon of forces.**
 4. **Resultant** = vector from the starting point to the end tip.
 5. **Measure length** using the same scale to get magnitude.
 6. **Measure angle** with respect to X-axis using protractor.
- This method gives a visual solution of resultant force.

- (b)** Derive relation between uniformly distributed load, shear force and bending moment with usual notations. **04**

Answer:

♦ **Shear Force–Load Relationship:**

From equilibrium of a small element of length dx :

$$\frac{dV}{dx} = -w$$
$$\Rightarrow V = -wx + C_1$$

So, slope of shear force diagram is equal to intensity of UDL (negative)

♦ **Bending Moment–Shear Force Relationship:**

From mechanics of beam:

$$\frac{dM}{dx} = V$$
$$\Rightarrow M = \int V dx + C_2$$

So, slope of bending moment diagram equals shear force at that point.

♦ **Final Relationships:**

$$\boxed{\frac{dV}{dx} = -w} \quad \text{and} \quad \boxed{\frac{dM}{dx} = V}$$

These equations form the basis for constructing SF and BM diagrams.

Answer:

◆ **Given:**

- Beam: Fixed at A, free at C
- UDL = 40 kN/m over AB = 3 m

⇒ Total load = $w \cdot L = 40 \cdot 3 = 120 \text{ kN}$, acts at center of AB (1.5 m from A)

- Point load = 10 kN at point C
- Span: AB = 3 m, BC = 2 m ⇒ Total length = 5 m

◆ **Step 1: Reactions at A**

Let:

- R_A = vertical reaction
- M_A = fixed end moment

Take moment about A:

$$M_A = (120 \times 1.5) + (10 \times 5) = 180 + 50 = \boxed{230 \text{ kNm}}$$

Now, vertical reaction:

$$R_A = 120 + 10 = \boxed{130 \text{ kN}}$$

◆ **Step 2: Shear Force Diagram (SFD)**

Start from left (A):

- From A to B (0 to 3 m):

$$SF = R_A - w \cdot x = 130 - 40x \rightarrow \text{linear drop}$$

At B:

$$SF = 130 - 40 \cdot 3 = 130 - 120 = 10 \text{ kN}$$

- From B to C (3 to 5 m):
SF drops by 10 kN at C ⇒ final SF = 0 (Free end)

◆ **Step 3: Bending Moment Diagram (BMD)**

At C (free end):

BM=0

From C to B:

- Linear rise (due to point load)
- At B ($x = 3 \text{ m}$):

$$BM_B = (10 \cdot 2) = 20 \text{ kNm}$$

From B to A (due to UDL):

Use general BM equation from A to x:

$$M(x) = M_A - R_A \cdot x + \frac{wx^2}{2}$$

$$M(x) = 230 - 130x + 20x^2$$

At B ($x = 3$):

$$M(3) = 230 - 130 \cdot 3 + 20 \cdot 9 = 230 - 390 + 180 = \boxed{20 \text{ kNm}}$$

So, BMD goes from 230 at A → 20 at B → 0 at C.

◆ **Final Answers (for diagram reference):**

- **Reactions:**

$$R_A = 130 \text{ kN}, M_A = 230 \text{ kNm}$$

- **SFD:**
 - Linear drop from 130 kN at A to 10 kN at B (due to UDL)
 - Sudden drop to 0 at C (due to point load)
- **BMD:**
 - Parabolic drop from 230 kNm at A to 20 kNm at B
 - Linear drop from 20 kNm at B to 0 at C

OR

Q.3 (a) Define (i) Shear force (ii) Point of zero shear (iii) Point of contraflexure

03

Answer:

(i) Shear Force:

Shear force at a section of a beam is the algebraic sum of all vertical forces acting either to the left or right of the section.

$$\text{Shear Force} = \sum \text{Vertical Forces}$$

(ii) Point of Zero Shear:

The location on a beam where the shear force changes sign (from positive to negative or vice versa). This point typically coincides with the location of **maximum bending moment**.

(iii) Point of Contraflexure:

The point along a beam where the **bending moment is zero** and changes sign. It occurs in overhanging or continuous beams. At this point, the curvature of the beam changes direction.

(b) State assumption made in theory of pure bending.

04

Answer:

Assumptions in Pure Bending Theory (Euler–Bernoulli Beam Theory):

1. **Beam is initially straight and has constant cross-section.**
2. **Material of the beam is homogeneous and isotropic.**
3. **Modulus of elasticity is the same in tension and compression.**
4. **Plane sections remain plane after bending.**
5. **Stress is proportional to strain (Hooke's law is valid).**
6. **No shear stress acts on the cross-section (pure bending).**
7. **Radius of curvature is large compared to depth of the beam.**

These assumptions help derive the **bending equation**:

$$\frac{M}{I} = \frac{\sigma}{y} = \frac{E}{R}$$

(c) Find centroid of lamina shown in fig. 7

07

Answer:

Description of Fig.7:

- Sector with radius = 100 mm (i.e., $\frac{1}{4}$ of a circle or 90° sector)

- Height = 100 mm (suggests vertical bounding rectangle)
- Hole: 50 mm diameter circular hole at 100 mm radius from center

Approach:

Use **composite area method**, with:

1. **Large circular sector (positive area)**
2. **Circular hole (negative area)**

Step 1: Area of Sector (A_1)

$$\text{Angle} = 90^\circ = \frac{\pi}{2} \text{ rad}, \quad r = 100 \text{ mm}$$

$$A_1 = \frac{1}{4}\pi r^2 = \frac{1}{4} \cdot \pi \cdot (100)^2 = 7854 \text{ mm}^2$$

Centroid of sector (from center along bisector):

$$\bar{x}_1 = \bar{y}_1 = \frac{2r}{3\pi} = \frac{200}{3\pi} \approx 21.22 \text{ mm}$$

Step 2: Area of Hole (A_2)

$$r = 25 \text{ mm}, \quad A_2 = -\pi r^2 = -\pi(25)^2 = -1963.5 \text{ mm}^2$$

Coordinates of center of hole (from figure):

- X-direction: 100 mm (on arc)
- Y-direction: 0 mm (center at bottom of arc)

So:

$$x_2 = 100 \cos(45^\circ) = 70.71 \text{ mm}$$

$$y_2 = 100 \sin(45^\circ) = 70.71 \text{ mm}$$

Step 3: Use Composite Centroid Formula

$$\bar{X} = \frac{A_1 x_1 + A_2 x_2}{A_1 + A_2}, \quad \bar{Y} = \frac{A_1 y_1 + A_2 y_2}{A_1 + A_2}$$

Substitute:

- $A_1 = 7854, x_1 = 21.22$
- $A_2 = -1963.5, x_2 = 70.71$

Compute $\bar{X}$:

$$\begin{aligned} \bar{X} &= \frac{(7854)(21.22) + (-1963.5)(70.71)}{7854 - 1963.5} \\ &= \frac{166675.88 - 138895.19}{5890.5} = \frac{27780.69}{5890.5} = \boxed{4.72 \text{ mm}} \end{aligned}$$

Compute $\bar{Y}$ (Same):

$$\bar{Y} = \frac{(7854)(21.22) + (-1963.5)(70.71)}{5890.5} = \boxed{4.72 \text{ mm}}$$

✓ Final Answer :

The centroid of the lamina is located at:

$$\boxed{(\bar{X}, \bar{Y}) = (4.72 \text{ mm}, 4.72 \text{ mm})}$$

from the vertex (O) along both axes

Q.4 (a) State and explain Pappus Guldinus first theorem using appropriate example. **03**

Answer:

♦ **Pappus–Guldinus First Theorem (Surface Area Theorem):**

Statement:

The surface area generated by rotating a plane curve (line) about an external axis (in its plane, not intersecting the curve) is equal to the product of the **length of the curve** and the **distance travelled by its centroid** during rotation.

$$A = L \cdot 2\pi R$$

Where:

- A = Surface area generated
- L = Length of the curve
- R = Distance of centroid from axis of rotation

♦ **Example:**

Find the surface area of a semicircular arc of radius r rotated about the x-axis:

- Length $L = \pi r$
- Centroid from center = $\frac{2r}{\pi}$
- Distance from axis = $R = \frac{2r}{\pi}$

$$A = \pi r \cdot 2\pi \cdot \frac{2r}{\pi} = 4\pi r^2$$

(b) A rectangular beam 300 mm deep is simply supported over a span of 4.0 m. **04**
What uniformly distributed load the beam may carry if the bending stress is not to exceed 120 MPa? Take $I = 8 \times 10^6 \text{ mm}^4$

Answer:

Given:

- Depth, $d = 300 \text{ mm}$
- Span, $l = 4.0 \text{ m} = 4000 \text{ mm}$
- $\sigma_{\max} = 120 \text{ MPa} = 120 \text{ N/mm}^2$
- Moment of inertia, $I = 8 \times 10^6 \text{ mm}^4$

♦ **Step 1: Max BM for simply supported beam under UDL:**

$$M_{\max} = \frac{w \cdot l^2}{8}$$

♦ **Step 2: Use bending stress formula:**

$$\sigma = \frac{M \cdot y}{I} \Rightarrow M = \frac{\sigma \cdot I}{y}$$

Where $y=d/2=150$ mm

$$M = \frac{120 \cdot 8 \times 10^6}{150} = \frac{960 \times 10^6}{150} = 6.4 \times 10^6 \text{ Nmm} = 6.4 \text{ kNm}$$

♦ **Step 3: Use BM to find www**

$$M = \frac{wl^2}{8} \Rightarrow w = \frac{8M}{l^2} = \frac{8 \cdot 6.4 \times 10^6}{(4000)^2}$$

$$= \frac{51.2 \times 10^6}{16 \times 10^6} = \boxed{3.2 \text{ N/mm}} = \boxed{3.2 \text{ kN/m}}$$

- (c) Calculate stresses in each portion and the total change in length for steel bar ABCD as shown in figure 8. Take $E = 200$ GPa 07

Answer:

Given (From Fig. 8):

The steel bar is divided into **three segments**, with **different cross-sections and loads**:

Segment	Length (L)	Diameter (d)	Load (P)	Nature
AB	600 mm	20 mm	80 kN (←)	Tension
BC	800 mm	32 mm	90 kN (→)	Compression
CD	600 mm	25 mm	60 kN (←)	Tension

- Take $E = 200 \text{ GPa} = 200 \times 10^3 \text{ N/mm}^2$

♦ **Step 1: Find Area of Each Portion**

$$A = \frac{\pi}{4} d^2$$

- AB:**

$$A_1 = \frac{\pi}{4} (20)^2 = 314.16 \text{ mm}^2$$

- BC:**

$$A_2 = \frac{\pi}{4} (32)^2 = 804.25 \text{ mm}^2$$

- CD:**

$$A_3 = \frac{\pi}{4} (25)^2 = 490.87 \text{ mm}^2$$

♦ **Step 2: Determine Nature and Net Internal Forces**

Let's check equilibrium to determine actual **internal forces** (we follow section-wise analysis):

- Section AB:**

External pull = 80 kN ($\rightarrow$), so bar is in **tension**

$$P_1 = 80 \times 10^3 \text{ N}$$

- **Section BC:**

Net pull from AB and CD = 80 ($\leftarrow$), 60 ($\leftarrow$)

But central portion gets **compressed** between two pulls

$$P_2 = 90 \times 10^3 \text{ N (compression)}$$

- **Section CD:**

Pulling force at right end = 60 kN ($\rightarrow$), hence **tension**

$$P_3 = 60 \times 10^3 \text{ N}$$

- ◆ **Step 3: Calculate Stress in Each Portion**

$$\sigma = \frac{P}{A}$$

- **AB:**

$$\sigma_1 = \frac{80 \times 10^3}{314.16} = \boxed{254.6 \text{ MPa (Tension)}}$$

- **BC:**

$$\sigma_2 = \frac{90 \times 10^3}{804.25} = \boxed{111.9 \text{ MPa (Compression)}}$$

- **CD:**

$$\sigma_3 = \frac{60 \times 10^3}{490.87} = \boxed{122.2 \text{ MPa (Tension)}}$$

- ◆ **Step 4: Calculate Elongation or Contraction**

Use:

$$\Delta L = \frac{P \cdot L}{A \cdot E}$$

AB:

$$\Delta L_1 = \frac{80 \cdot 10^3 \cdot 600}{314.16 \cdot 200 \cdot 10^3} = \frac{48 \cdot 10^6}{62.83 \cdot 10^6} = 0.763 \text{ mm } (\uparrow)$$

BC (Compression):

$$\Delta L_2 = \frac{90 \cdot 10^3 \cdot 800}{804.25 \cdot 200 \cdot 10^3} = \frac{72 \cdot 10^6}{160.85 \cdot 10^6} = 0.447 \text{ mm } (\downarrow)$$

CD:

$$\Delta L_3 = \frac{60 \cdot 10^3 \cdot 600}{490.87 \cdot 200 \cdot 10^3} = \frac{36 \cdot 10^6}{98.17 \cdot 10^6} = 0.3667 \text{ mm } (\uparrow)$$

- ◆ **Step 5: Total Change in Length**

Add elongation and subtract contraction:

$$\begin{aligned} \Delta L_{\text{total}} &= \Delta L_1 - \Delta L_2 + \Delta L_3 \\ &= 0.763 - 0.447 + 0.3667 = \boxed{0.6827 \text{ mm (Extension)}} \end{aligned}$$

✓ **Final Answers:**

Segment	Stress (MPa)	Nature
AB	254.6	Tension
BC	111.9	Compression
CD	122.2	Tension

- **Total change in length = 0.683 mm (Extension)**

OR

Q.4 (a) Define : (i) Shear Stress (ii) Modulus of Rigidity (iii) Volumetric strain

03

Answer:

(i) Shear Stress (τ):

Shear stress is the internal resistance per unit area offered by a material when it is subjected to tangential forces.

$$\tau = \frac{F}{A} \quad (\text{Units: N/mm}^2)$$

Where:

- F = tangential force
- A = area resisting the force

(ii) Modulus of Rigidity (G):

Also called **Shear Modulus**, it is the ratio of shear stress to the corresponding shear strain within elastic limits.

$$G = \frac{\tau}{\gamma}$$

Where:

- τ = shear stress
- γ = shear strain

(iii) Volumetric Strain:

It is the **change in volume per unit original volume** of a material under stress.

$$\epsilon_v = \frac{\Delta V}{V}$$

(b) Determine moment of inertia about its horizontal centroidal axis for T section having flange and web dimensions 100mm x20 mm each.

04

Answer:

◆ **Given:**

- Flange: 100 mm × 20 mm
 - Web: 100 mm × 20 mm
 - Both centered (web below flange)
- We'll use **composite section method**.

◆ **Step 1: Split the section into two rectangles:**

Part	Dimensions (b × h)	Area (A)	y (from base)
1 (Flange)	100 × 20 mm	A ₁ =2000 mm ²	y ₁ =120 mm
2 (Web)	20 × 100 mm	A ₂ =2000 mm ²	y ₂ =50 mm

Total height = 20 + 100 = 120 mm

◆ **Step 2: Find centroid $\bar{y}$ from bottom:**

$$\bar{y} = \frac{A_1 y_1 + A_2 y_2}{A_1 + A_2} = \frac{2000 \cdot 120 + 2000 \cdot 50}{4000} = \frac{240000 + 100000}{4000} = 85 \text{ mm}$$

◆ **Step 3: Moment of Inertia about horizontal centroidal axis using parallel axis theorem:**

$$I = I_{\text{centroid}} + Ad^2$$

Flange:

$$I_1 = \frac{bh^3}{12} + A(y_1 - \bar{y})^2$$

$$= \frac{100 \cdot 20^3}{12} + 2000 \cdot (120 - 85)^2 = 66,667 + 2,450,000 = 2,516,667 \text{ mm}^4$$

Web:

$$I_2 = \frac{bh^3}{12} + A(y_2 - \bar{y})^2$$

$$= \frac{20 \cdot 100^3}{12} + 2000 \cdot (85 - 50)^2 = 1,666,667 + 2,450,000 = 4,116,667 \text{ mm}^4$$

◆ **Final Answer:**

$$I_{xx} = I_1 + I_2 = 2,516,667 + 4,116,667 = 6.63 \times 10^6 \text{ mm}^4$$

- (c) A short concrete column 300mm x 300mm in section is carrying axial load of 360 kN. The column is reinforced by four 12mm diameter steel bars each one at corner. Calculate stresses in concrete and steel. Take $E_c = 14\text{GPa}$ and $E_s = 210\text{GPa}$.

07

Answer:

◆ **Given:**

- Concrete section = 300 mm × 300 mm
- Load $P = 360$ kN
- Reinforcement: 4 bars, 12 mm diameter each (placed in corners)
- $E_c = 14$ GPa, $E_s = 210$ GPa

◆ **Step 1: Cross-sectional Areas**

- **Concrete area:**

$$A_c = 300 \cdot 300 = 90,000 \text{ mm}^2$$

- **Steel area (4 bars):**

$$A_s = 4 \cdot \frac{\pi}{4} \cdot (12)^2 = 4 \cdot 113.1 = 452.4 \text{ mm}^2$$

- **Net concrete area (excluding steel):**

$$A'_c = A_c - A_s = 90,000 - 452.4 = 89,547.6 \text{ mm}^2$$

◆ **Step 2: Modular Ratio (m):**

$$m = \frac{E_s}{E_c} = \frac{210}{14} = 15$$

◆ **Step 3: Equivalent Area**

Convert steel area into equivalent concrete area:

$$A_{eq} = A'_c + mA_s = 89,547.6 + 15 \cdot 452.4 = 89,547.6 + 6786 = 96,333.6 \text{ mm}^2$$

◆ **Step 4: Stress in Concrete**

$$\sigma_c = \frac{P}{A_{eq}} = \frac{360 \times 10^3}{96,333.6} = \boxed{3.736 \text{ MPa}}$$

◆ **Step 5: Stress in Steel**

$$\sigma_s = m \cdot \sigma_c = 15 \cdot 3.736 = \boxed{56.04 \text{ MPa}}$$

✓ **Final Answers (Q.4 OR (c)):**

- **Stress in Concrete = 3.736 MPa**
- **Stress in Steel = 56.04 MPa**

Q.5 (a) Sketch qualitative shear stress distribution diagrams for following sections
(i) Circular (ii) I section and (iii) T section

03

Answer:

◆ **(i) Circular Section:**

- Shear stress is **maximum at the neutral axis (center)** and **zero at outer surface**.
- Follows **parabolic distribution**.

 Sketch: Semi-ellipse shape, symmetric about center

♦ **(ii) I-Section:**

- Most shear is carried by **web**; very little by flanges.
- Shear stress is almost **uniform in web**, and **very small in flange**.

 Sketch: Narrow rectangle at web, negligible in flange

♦ **(iii) T-Section:**

- Similar to I-section but asymmetric.
- Maximum shear is in **web**, and **top flange carries some**.

 Sketch: Asymmetric web with larger top

- (b) A steel tube of 2 m length is subjected to 50° C rise in temperature. Determine 04
- (i) free natural expansion and (ii) stress developed in the tube, if expansion is prevented. Take $E_s = 2.0 \times 10^5 \text{ N/mm}^2$ and $\alpha = 12 \times 10^{-6} \text{ per } ^\circ \text{C}$.
-

Answer:

♦ **(i) Free Expansion:**

$$\Delta L = \alpha \cdot L \cdot \Delta T = 12 \times 10^{-6} \cdot 2000 \cdot 50 \\ = 1.2 \text{ mm}$$

✓ **Free expansion = 1.2 mm**

♦ **(ii) Stress if expansion is prevented:**

Use thermal stress formula:

$$\sigma = \alpha \cdot E \cdot \Delta T = 12 \times 10^{-6} \cdot 2 \times 10^5 \cdot 50 \\ = 120 \text{ N/mm}^2$$

✓ **Thermal stress = 120 MPa (compressive)**

- (c) Define: (i) Poisson's ratio (ii) Bulk modulus (iii) Modulus of Elasticity. 07
- Derive relation between bulk modulus, Poisson's ratio and modulus of elasticity.
-

Answer:

(i) Poisson's Ratio (μ):

Ratio of **lateral strain to longitudinal strain** in a stretched material.

$$\mu = \frac{\text{Lateral Strain}}{\text{Longitudinal Strain}}$$

♦ **(ii) Bulk Modulus (K):**

The ratio of **hydrostatic pressure to volumetric strain**.

$$K = \frac{\text{Stress (Pressure)}}{\text{Volumetric Strain}}$$

♦ **(iii) Modulus of Elasticity (E):**

The ratio of **normal stress to longitudinal strain** (Young's modulus).

$$E = \frac{\sigma}{\epsilon}$$

◆ **Derivation of Relation:**

Under triaxial stress condition (equal pressure from all directions), longitudinal and lateral strains add up to volumetric strain.

Volumetric strain (ϵ_v):

$$\epsilon_v = 3\epsilon(1 - 2\mu)$$

Since:

$$E = \frac{\sigma}{\epsilon} \Rightarrow \epsilon = \frac{\sigma}{E}$$

Then:

$$\epsilon_v = 3 \cdot \frac{\sigma}{E}(1 - 2\mu)$$

But:

$$K = \frac{\sigma}{\epsilon_v}$$

Substitute:

$$K = \frac{\sigma}{3 \cdot \frac{\sigma}{E}(1 - 2\mu)} = \frac{E}{3(1 - 2\mu)}$$

✓ **Final Relation:**

$$K = \frac{E}{3(1 - 2\mu)}$$

OR

Q.5 (a) Define (i) Torsional Rigidity (ii) Principal Plane (iii) Neutral axis

03

Answer:

◆ **(i) Torsional Rigidity (GJ):**

It is the **resistance offered by a shaft** to twisting. It is the product of the **modulus of rigidity (G)** and **polar moment of inertia (J)**.

$$\text{Torsional Rigidity} = GJ$$

◆ **(ii) Principal Plane:**

A principal plane is a plane **within a stressed body** where the shear stress is **zero** and the normal stresses reach **maximum or minimum** values (called **principal stresses**).

◆ **(iii) Neutral Axis:**

It is an imaginary axis in a beam cross-section where the **bending stress is zero** during bending. It passes through the **centroid of the cross-section**.

(b) A solid steel shaft of 60 mm diameter is subjected to torque of 5 kNm. Determine maximum shear stress developed in the shaft. $G = 80 \text{ GPa}$

04

Answer:

Given:

- $d = 60 \text{ mm}$,
- $T = 5 \text{ kNm} = 5000 \text{ Nm} = 5 \times 10^6 \text{ Nmm}$
- $G = 80 \text{ GPa} = 80 \times 10^3 \text{ N/mm}^2$

♦ **Step 1: Use torsion formula:**

$$\tau_{\max} = \frac{16T}{\pi d^3}$$
$$\tau_{\max} = \frac{16 \cdot 5 \times 10^6}{\pi \cdot (60)^3} = \frac{80 \times 10^6}{678585} = \boxed{117.9 \text{ N/mm}^2}$$

(c) For an element shown in fig.9.

07

Determine (i) Principal stresses and location of corresponding principal planes.
(ii) Maximum shear stress and location of planes containing it

Answer:

♦ **Given Stresses (From Fig. 9):**

- $\sigma_x = 40 \text{ N/mm}^2$
- $\sigma_y = 100 \text{ N/mm}^2$
- $\tau_{xy} = 60 \text{ N/mm}^2$ (clockwise shear)

♦ **Step 1: Principal Stresses**

Use formulas:

$$\sigma_{1,2} = \frac{\sigma_x + \sigma_y}{2} \pm \sqrt{\left(\frac{\sigma_x - \sigma_y}{2}\right)^2 + \tau_{xy}^2}$$
$$= \frac{40 + 100}{2} \pm \sqrt{\left(\frac{40 - 100}{2}\right)^2 + 60^2}$$
$$= 70 \pm \sqrt{(-30)^2 + 3600} = 70 \pm \sqrt{900 + 3600}$$
$$= 70 \pm \sqrt{4500} = 70 \pm 67.08$$

$$\boxed{\sigma_1 = 137.08 \text{ N/mm}^2}, \quad \boxed{\sigma_2 = 2.92 \text{ N/mm}^2}$$

♦ **Step 2: Orientation of Principal Planes**

$$\tan 2\theta = \frac{2\tau_{xy}}{\sigma_x - \sigma_y} = \frac{2 \cdot 60}{40 - 100} = \frac{120}{-60} = -2 \Rightarrow 2\theta = \tan^{-1}(-2) = -63.43^\circ \Rightarrow \theta = -31.72^\circ$$

✓ Principal planes are at -31.72° and $+58.28^\circ$ w.r.t. horizontal

◆ Step 3: Maximum Shear Stress

$$\tau_{\max} = \sqrt{\left(\frac{\sigma_x - \sigma_y}{2}\right)^2 + \tau_{xy}^2}$$

$$= \sqrt{(-30)^2 + 60^2} = \sqrt{900 + 3600} = \boxed{67.08 \text{ N/mm}^2}$$

◆ Orientation of Shear Stress Planes:

Shear stress is **maximum** at planes 45° from principal planes, i.e.,

$$\theta_{\tau_{\max}} = -31.72^\circ + 45^\circ = \boxed{13.28^\circ}$$

✓ Final Answers (Q.5 OR (c)):

Quantity	Value
σ_1	137.08 N/mm ² (major principal)
σ_2	2.92 N/mm ² (minor principal)
Max shear stress τ	67.08 N/mm ²
Principal plane angle	-31.72°
Max shear plane angle	13.28°




Fig. 1




Fig. 3




Fig. 2




Fig. 4




Fig. 5




Fig. 6




Fig. 8




Fig. 7




Fig. 9
